

## PRODUCT INFORMATION

Information requirements for boiler space heaters, boiler combination heaters and cogeneration space heaters  
(COMMISSION DELEGATED REGULATIONS No. 811-814/2013)

Model(s):	<b>C32SPV24MEFB-S-ERP, SIGMA 24 TF</b>		
Condensing boiler [yes/no]:	no		
Low-temperature (**) boiler [yes/no]:	no		
B1 boiler [yes/no]:	no		
Cogeneration space heater [yes/no]:	no	If yes, equipped with a supplementary heater: [yes/no]: no	

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output</b>	$P_{rated}$	24	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	81	%
For boiler space heaters and boiler combination heaters: Useful heat output				For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$P_4$	23,5	kW	At rated heat output and high-temperature regime (*)	$\eta_4$	83,7	%
At 30 % of rated heat output and low-temperature regime (**)	$P_1$	7,5	kW	At 30 % of rated heat output and low-temperature regime (**)	$\eta_1$	82,8	%
<b>Auxiliary electricity consumption</b>				<b>Other items</b>			
At full load	$e_{lmax}$	0,082	kW	Standby heat loss	$P_{stby}$	0,4	kW
At part load	$e_{lmin}$	0,070	kW	Ignition burner power consumption	$P_{ign}$	0,0	kW
In standby mode	$P_{SB}$	0,003	kW	Emissions of nitrogen oxides	$NO_x$	100	mg/kWh
				Noise level	$LWA$	48	dB

For combination heaters:							
<b>Declared load profile</b>	M			<b>Water heating energy efficiency</b>	$\eta_{wh}$	76	%
Daily electricity consumption	$Q_{elec}$	0,200	kWh	Daily fuel consumption	$Q_{fuel}$	7,150	kWh
Annual electricity consumption	$AEC$	44	kWh	Annual fuel consumption	$AFC$	6	GJ

Contact details: [office.vaduri@kober.ro](mailto:office.vaduri@kober.ro)  
www.motan.ro  
Telephone: 0233 241746  
Fax: 0233 241929

Name and address of the manufacturer: KÖBER Ltd VADURI Branch, Piatra Neamt town, Neamt District, Romania

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Seasonal space heating energy efficiency class:

**C**

Water heating energy efficiency class:

**A**

KÖBER Ltd Vaduri Branch, 10.08.2018

Branch Manager  
eng. Theodor Farcas

STR. ZORELELOR NR. 25, SAT  
VADURI, COMUNA ALEXANDRU CEL  
BUN, JUDETUL NEAMT, ROMANIA,  
COD POSTAL 617511  
C.I.F. RO2005144  
BCR: RO53 RNCB 0196 0277 8883 0005  
BTRL:RO79 BTRL 0280 1202 3631 46XX

**KÖBER SRL DUMBRAVA ROSIE  
SUCURSALA VADURI**

TEL : 0040-233-241746  
0040-233-241933  
FAX : 0040-233-241929

E-mail : [office.vaduri@kober.ro](mailto:office.vaduri@kober.ro)  
Url : [www.motan.ro](http://www.motan.ro)